

# CERTIFICATE OF CONFORMITY

We hereby certify that the following item complies with the features listed below.

#### **Item**

Reference SFERACO Fig. 1118

Description CARBON STEEL TRIPLE OFFSET BUTTERFLY VALVE LUG - from DN100 to DN300

#### **Main features**

Body A216WCB

Closure member Disc CF8M + Stellite ® Gr.6

Seat A479 XM-19 + graphite

Connections Lug type, between flanges PN40

Face to face EN 558 series 109

Specifications ISO pad, Full crossing stem, Bidirectional

## **Operating conditions**

Fluids Heating, geothermics, industrial cold, shipbuilding, petrochemical

PS 40 bar, Steam: 30 bar max.

TS -39°C to +349°C

### **Standards**

## 2014/68/EU Directive - Risk category III / Module H - Notified body: CE 0035

Quality management according to ISO 9001:2015

After Examination, the equipment was found not to be in the scope of the ATEX Directive 2014/34/EU. It has no own potential source of ignition.

Fire safe according to ISO 10497: 2010

Fugitive Emissions according to EN 15848-1: 2006 Class C

SIL 2 according to IEC/EN 61508, SIL 3 capable following the installation

# **Product guarantee**

### 2 years

Technical Director St-Quentin-Fallavier, France, 2 May 2025

