

## CERTIFICATE OF CONFORMITY

*We hereby certify that the following item complies with the features listed below.*

### Item

Reference **SECTORIEL Fig. 710XS**  
Description **CARBON STEEL BALL VALVE 3PC - from DN15 to DN100**

### Main features

Body **A216WCB**  
Closure member **Ball CF8M**  
Seat **PTFE+ stainless steel**  
Connections **RF PN40**  
Face to face **EN 558 series 1**  
Specifications **Full bore, Anti-blowout stem, Locking device, Antistatic device, ISO pad**

### Operating conditions

Fluids **All compatible fluids**  
PS **40 bar, steam: 15 bar max.**  
TS **-25°C to +220°C, steam +200°C max.**

### Standards

**2014/68/EU Directive – Risk category II / Module H** - Notified body : CE 0035

Quality management according to ISO 9001:2015

After Examination, the equipment was found not to be in the scope of the ATEX Directive 2014/34/EU. It has no own potential source of ignition.

Fire safe API 607/5 – ISO 10497-5

TA-LUFT VDI 2440 DCI 3.3.1.3

Safety integrity level certification SIL 2 according to IEC/EN 61508, SIL 3 capable following the installation

### Product guarantee

**2 years**

Technical Director  
St-Quentin-Fallavier, France, 2 May 2025



**SYVECO**  
107 rue du Ruisseau  
38070 Saint-Quentin-Fallavier - FRANCE  
+33 474 948 650 | info@syveco.com  
VAT : FR 92 487 897 449