

BRONZE UNION BONNET GLOBE VALVE METAL DISC FEMALE BSP PN25

Bronze union bonnet globe valve female BSP with reduced bore for closing or setting networks of heating, water distribution and watering, compressed air.

PTFE packing.

Monobloc bronze body provides excellent corrosion resistance.



Size : DN1/4" to DN2"

Connection : Female BSP

Min Temperature : -10°C

Max Temperature : +180°C

Max Pressure : 25 Bars

Specifications : Rising rotating stem and handwheel
Monobloc
Reduced bore
PTFE packing
Stainless steel disc and seat

Materials : Bronze ASTM B62 body

BRONZE UNION BONNET GLOBE VALVE METAL DISC FEMALE BSP PN25

SPECIFICATIONS :

- Respect the flow direction (indicated by the arrow)
- Rising rotating stem and handwheel
- PTFE packing
- Bronze body with union bonnet
- Stainless steel seat and disc
- Threaded female BSP cylindrical


USE :

- Heating, water distribution, watering, compressed air
- Min and max Temperature Ts : - 10°C to + 180°C
- Max Pressure Ps : 25 bars (see graph)

PRESSURE / TEMPERATURE GRAPH :

PRESSURE


Bar



TEMPERATURE

BRONZE UNION BONNET GLOBE VALVE METAL DISC FEMALE BSP PN25

HEAD LOSS GRAPH :




RANGE :

- Globe valve bronze body and stainless steel disc, female threaded cylindrical BSP from DN1/4" to DN2" **Ref. 451**

BRONZE UNION BONNET GLOBE VALVE METAL DISC FEMALE BSP PN25


MATERIALS :



Item	Designation	Materials
1	Body	Bronze C83600 ASTM B62
2	Bonnet	Brass CW 617N according to EN 12165
3	Bonnet nut	Brass CW 617N according to EN 12165
4	Seat	AISI 316L
5	Disc	
6	Washer ring	Brass CW 614N according to EN 12164
7	Stem	Brass CW 614N according to EN 12164
8	Packing DN 1/4" – 1/2"	PTFE
8	Packing DN 3/4" – 2"	High temperature Fiber AF/15/MA
9	Packing gland	Brass CW 614N according to EN 12164
10	Packing nut	Brass CW 614N according to EN 12164
11	Handwheel	Aluminium GD12FE UNI EN 1706
12	Handwheel nut	Steel S6 UNI 5589

BRONZE UNION BONNET GLOBE VALVE METAL DISC FEMALE BSP PN25

SIZE (in mm) :



DN	1/4"	3/8"	1/2"	3/4"	1"	1"1/4	1"1/2	2"
L	46	46	56	62	74	91	100	128
H	86	86	105	128	143	165	180	210
Ø P	10.8	10.8	12.5	18	20	30	30	37
Ø V	50	50	55	60	70	80	80	95
Weight (Kg)	0.27	0.28	0.36	0.65	0.90	1.42	1.79	2.98
Ref.	451002	451003	451004	451005	451006	451007	451008	451009

BRONZE UNION BONNET GLOBE VALVE METAL DISC FEMALE BSP PN25**STANDARDS :**

- Manufacturer certified ISO 9001 : 2015 and ISO 14001 : 2015
- DIRECTIVE 2014/68/EU : For liquids and gas of Group 1
 - DN1/4"-1" : Article 4, §3 (SEP), no CE marking
 - DN1"1/4-1"1/2 : Risk Category I, CE marking
 - DN2" : Risk Category II, CE0497 marking
- Pressure tests according to EN 12266-1, Rate A
- Threaded female BSP cylindrical according to ISO 228-1

ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.
The customer must check the right choice of the products with the real service conditions.