

STAINLESS STEEL GLOBE VALVE THREADED FEMALE BSP PN16

Stainless steel globe valve female bsp reduced bore for closing or setting network of chemical industries, petrochemical industries, hydraulic installation, heating, water distribution.

PTFE packing and gasket.

Monoblock design for a better mechanical resistance.

Valve in accordance with the regulation (EC) N° 1935/2004 on request.

FDA PTFE gaskets.

Certificate
3.1



FDA

CE 1935/2004



LRQA

PED/2014/68/UE



Size : DN1/2" to DN2"

Connection : Female BSP

Min Temperature : -20°C

Max Temperature : +180°C

Max Pressure : 16 Bars

Specifications : Rising rotating stem and handwheel
Monoblock
Reduced bore
PTFE packing

Materials : Stainless steel EN 1.4408

STAINLESS STEEL GLOBE VALVE THREADED FEMALE BSP PN16

SPECIFICATIONS :

- Respect the flow direction (indicated by the arrow)
- Rising rotating stem and handwheel
- PTFE packing
- Stainless steel EN 1.4408 body
- Reduced bore
- Threaded female BSP cylindrical


USE :

- Chemical and pharmaceutical industries, petrochemical industries, hydraulic installation
- Min and max Temperature Ts : - 20°C to + 180°C
- Max Pressure Ps : 16 bars (see graph)
- **Do not use for steam**

PRESSURE / TEMPERATURE GRAPH (STEAM EXCLUDED) :

PRESSURE


BAR



STAINLESS STEEL GLOBE VALVE THREADED FEMALE BSP PN16

HEAD LOSS GRAPH :

(Bar)



FLOW COEFFICIENT Kvs (M3 / h) :

DN	1/2"	3/4"	1"	1"1/4	1"1/2	2"
Kvs (m3/h)	1.88	3.06	5.67	9.05	15.18	24.94

NUMBER OF TURNS FOR CLOSING OR OPENING :


DN	1/2"	3/4"	1"	1"1/4	1"1/2	2"
Nb of turns	4.8	4.3	7	8.7	8.2	11

RANGE :

- Globe valve female threaded cylindrical BSP from DN1/2" to DN 2" **Ref. 485**

STAINLESS STEEL GLOBE VALVE THREADED FEMALE BSP PN16


MATERIALS :



Item	Designation	Materials
1	Body	EN 1.4408
2	Body seal	PTFE
3	Disc	AISI 316
4	Stem	
5	Bonnet	EN 1.4408
6	Packing	PTFE
7	Packing gland	AISI 304
8	Packing nut	ASTM A351 CF8M
9	Handwheel	Aluminium
10	Name plate	
11	Washer	AISI 316
12	Nut	AISI 304

STAINLESS STEEL GLOBE VALVE THREADED FEMALE BSP PN16

SIZE (in mm) :



DN	1/2"	3/4"	1"	1"1/4	1"1/2	2"
Ø d	12	15	20	25	32	40
L	52	60	72	81	90	101
L1	12.5	13	17.5	19	20	20
H (opened)	79	94	101	119	142	159
H (closed)	73	85	91	103	124	139
Ø V	70	70	80	80	90	100
Weight (Kg)	0.26	0.44	0.60	0.96	1.22	1.74
Ref.	485004	485005	485006	485007	485008	485009

STAINLESS STEEL GLOBE VALVE THREADED FEMALE BSP PN16**STANDARDS :**

- Manufacturer certified ISO 9001 : 2015
- DIRECTIVE 2014/68/EU : For liquids and gas of Group 1
 - DN1/4"-1" : Article 4, §3 (SEP), no CE marking
 - DN1"1/4-4" : Risk Category I, CE0038 or CE0343 marking
- Certificate 3.1 on request
- Pressure tests according to EN 12266-1, D Rate
- Threaded BSP female cylindrical according to ISO 228-1
- Valve in accordance with the regulation **(EC) N° 1935-2004 on request**
- FDA PTFE gaskets

ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.
The customer must check the right choice of the products with the real service conditions.