

CERTIFICATE OF CONFORMITY

We hereby certify that the following item complies with the features listed below.

Item

Reference SFERACO Fig. 713

Description STAINLESS STEEL BALL VALVE 3PC ISO PAD FIRE SAFE - from 1/4" to 4"

Main features

Body CF8M

Closure member Ball F316L

Seat PTFE

Connections BSP female/female or BW or SW Face to face DIN 3202-4 M3 (EN 16722)

Specifications Full bore, Anti-blowout stem, Antistatic device, ISO pad

Operating conditions

Fluids Chemical and pharmaceutical industries, petrochemical industries, hydraulic

installation, compressed air

PS **100** bar up to 3/8", 63 bar from 1/2" to 3/4", 40 bar from 1" to 2", 25 bar from

2"1/2 to 3", 20 bar above. Compressed air: 8 bar up to 2", 6 bar above. Steam: 6

bar up to 2", 6 bar above.

TS -28°C to +200°C

Standards

2014/68/EU Directive - Risk category II / Module H - Notified body: CE 0038 or 0094

Quality management according to ISO 9001:2015

After Examination, the equipment was found not to be in the scope of the ATEX Directive 2014/34/EU. It has no own potential source of ignition.

Fire safe according to ISO 10497 up to 3"

Fugitive emissions according to ISO 15848-1: 2003 Class A

Safety integrity level certification SIL 2 according to IEC/EN 61508, SIL 3 capable following the installation. NACE MR0175

Product guarantee

2 years

Technical Director St-Quentin-Fallavier, France, 2 May 2025

