

ELECTRIC BRASS BALL VALVE TYPE LYVA 2

FEATURES

The electric brass ball valve LYVA 2 is dedicated to the automatic shutt-off of small sizes fluids clear, unloaded and viscous fluids. The LYVA full bore valve, is perfect for applications such as water treatment, HVAC, industry, OEM, etc. where a traditional solenoid valve is not suitable. The operation of the actuator with 2 wires automatic position return through capacitor (RC) makes its installation and use very easy. Low power consumption. The LYVA 2 has got the CSF certificate for food contact and the french ACS certificate for use on potable water.



AVAILABLE MODELS

LYVA 2 : brass body

Sizes and connexions : G 1/2" to G 2".

Voltages : 24 Vac-cc, 230 Vac.


Wiring scheme : CR202, 2 wires, automatic position return through capacitor.

Power cable : 1,5 m

LIMITS OF USE

Use forbidden on groupe I gases according to CE 2014/68 directive

Use forbidden in explosive area.



Electric protection :	IP 67
PS fluid :	0 - 10 bar up to 1" 0 - 6 bar from 1"1/4 to 2"
ΔP max :	10 bar up to 1" 6 bar from 1"1/4 to 2"
TS fluid :	0°C / +90°C
TS ambient :	-10°C / +55°C

DIRECTIVES AND STANDARDS OF CONSTRUCTION


SUBJECT	Standard	SUBJECT	Standard
Pressure equipment CE 2014/68	A4 § 3	Material grade	EN 1503-4
Low voltage directive CE 2014/35	category I	Threaded connection	ISO 228
Food contact	NSF certificate	ACS potable water certificate	

Information given as an indication only, and subject to possible modifications

	SECTORIEL S.A. 45 rue du Ruisseau 38290 SAINT QUENTIN-FALLAVIER – FRANCE Tél : +33 4 74 94 90 70 - Fax : +33 4 74 94 13 95 www.sectoriel.com / Email : sectoriel@sectoriel.fr	Pages	1/3
		Ref.	TDS8920
		Rev.	10
		Date	09/2025

ELECTRIC BRASS BALL VALVE TYPE LYVA 2

WIRING DIAGRAM



INSTALLATION

All positions mounting excepted horizontal with pointing down actuator.

For a use on liquids, the installation of a upstream protection strainer is recommended.

OPTIONS


Other votages 5 Vcc, 9 Vcc, 36 Vcc, 110 Vca

Other wiring schemes (see below)

Manual override

Cover without position indicator

Normaly open version (NO)



Information given as an indication only, and subject to possible modifications



SECTORIEL S.A.
 45 rue du Ruisseau
 38290 SAINT QUENTIN-FALLAVIER – FRANCE
 Tél : +33 4 74 94 90 70 - Fax : +33 4 74 94 13 95
www.sectoriel.com / Email : sectoriel@sectoriel.fr

Pages	3/3
Ref.	TDS8920
Rev.	10
Date	09/2025