

ROTATING GATE VALVE LOCKOUT

Rotating Gate Valve Lockout Device for valve handles to surround the valve operating handle and protect against accidental valve opening.

The unique, patented rotating design allows for easier installation in confined space applications.

Tough, lightweight, dielectric Zenex™ Thermoplastic body withstands chemicals and performs effectively in extreme conditions.

Includes high-visibility permanent safety labels.

Possible to remove the central part for valves with rising stem.



Size : D.25 to 330

Connection : Direct on the handwheel

Min Temperature : -40°C

Max Temperature : +90°C

Specifications : Easy installation

Lockable up to 4 padlocks

Short length

Materials : Dielectric Zenex™ Thermoplastic body

ROTATING GATE VALVE LOCKOUT

SPECIFICATIONS :

- Rotating Gate Valve Lockout Device
- Outward/inward rotation allows for easier installation and storage
- Surrounds the valve operating handle to protect against accidental valve opening
- Unique patented rotating design allow for easier installation in confined space applications
- Each size rotates into itself and nests into the next larger size to save space in safety tool boxes
- Center knockout can be removed for rising stem gate valves
- Multiple workers can apply their personal safety padlocks
- Complete with high visibility permanent safety labels (English, French & Spanish) that can be written-on to identify the responsible person
- Tough, lightweight, dielectric thermoplastic bodies withstand chemicals

USE :

- For valves with handle
- Min and max temperature Ts : -40°C to + 90°C

RANGE :

Handwheel diameter (mm)	25-76	50-127	102-165	152-254	203-330
Depth (mm)	30	38	48	70	86
Stem opening (mm)	19	38	64	89	101
Number of Padlock	2	3	4	4	4
Weight (Kg)	0.2	0.35	0.55	1.2	2.21
Ref.	9848001	9848101	9848201	9848301	9848401

STANDARDS :

- Manufacturer certified ISO 9001 : 2015

ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.
The customer must check the right choice of the products with the real service conditions.