

CERTIFICATE OF CONFORMITY

We hereby certify that the following item complies with the features listed below.

Item

Reference SFERACO Fig. 1113

Description CARBON STEEL DOUBLE OFFSET BUTTERFLY VALVE WAFER - from DN50 to DN400

Main features

Body A216WCB

Closure member Disc CF8M

Seat **PTFE + graphite**

Connections Wafer type, Between flanges PN16 or PN25

Face to face EN 558 series 20

Specifications ISO pad, Full crossing stem, Locking device up to DN150

Operating conditions

Fluids Heating, geothermics, industrial cold, shipbuilding, petrochemical

PS 25 bar up to DN80, PN16 or PN25 up to DN300, PN25 above 25 bar, Steam: 10 bar

max.

TS -29°C to +250°C

Standards

2014/68/EU Directive - Risk category III / Module H - Notified body: CE 0035

Quality management according to ISO 9001:2015

After Examination, the equipment was found not to be in the scope of the ATEX Directive 2014/34/EU. It has no own potential source of ignition.

Fire safe according to ISO 10497: 2010

SIL 2 according to IEC/EN 61508, SIL 3 capable following the installation

Product guarantee

2 years

Technical Director St-Quentin-Fallavier, France, 2 May 2025

