

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

Resilient seat gate valve full and total bore for drinking water, water distribution.

Sliding pad to facilitating the wedge movement up to DN200.

3 NBR O ring on stem and NBR bonnet gasket.

Possibility to change stem gasket under pressure from DN80 to DN1000

EN 1074



Certificate

3.1



Size : DN40 to DN300

Connection : Flanges PN10/16

Min Temperature : -10°C

Max Temperature : +70°C

Max Pressure : 16 Bars

Specifications : Non rising stem

Anticlockwise to close (ATC)

Full and total bore

Materials : Ductile iron body EN GJS-500-7

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS


SPECIFICATIONS :

- Full and total bore
- Stainless steel non rising stem
- Anticlockwise to close (ATC)
- Sliding pad (to facilitating the wedge movement) up to DN200
- Ductile iron wedge EPDM ACS
- No retention area
- Heel positioning
- NBR bonnet gasket
- Screws bonnet protected
- 3 NBR O ring on stem
- Possibility to change stem gasket under pressure from DN80 to DN300
- Epoxy painting RAL 5005 color 250 µm thickness GSK certified
- Dust-coat on stem
- PN10/16 flanges R.F.

USE :

- For water distribution, drinking water
- Min and max Temperature Ts : - 10°C to + 70°C
- Max pressure Ps : 16 bars for PN16 flanged valves
- Max pressure Ps : 10 bars for PN10 flanged valves from DN200 to 300

HEAD LOSS GRAPH :



RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

FLOW COEFFICIENT Kvs (M3 / h) :

DN	40	50	65	80	100	125	150	200	250	300
Kvs (m3/h)	118	229	360	537	933	1595	2685	5004	8393	12072

HEAD LOSS CALCULATION FOR WATER :

$$\Delta p = (Q / Kvs)^2$$

Q : flow in m³/h

Δp : Head loss in bar

TORQUE VALUE (in Nm without safety coefficient) :

DN	40	50	65	80	100	125	150	200	250	300
Torque (Nm)	15	20	20	30	40	40	75	125	175	200

NUMBER OF CYCLES TO CLOSE OR OPEN THE VALVE :

DN	40	50	65	80	100	125	150	200	250	300
Number of cycles	13	14.5	18.75	21.5	21.5	24.5	30	34	45.25	49.75

RANGE :

- Ductile iron body with PN10/16 flanges R.F. and handwheel with EPDM ACS wedge **Ref. 191** from DN40 to DN300

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

ACCESSORIES :



- Possible with square drive nut (option) **Ref. 9801831-9801838**



- Stem extension 1 meter long **Ref. 9802020** from DN50 to DN300

- Stem extension 1,5 meter long **Ref. 9802042** from DN50 to DN300




- Stem extension 1,3 to 1,8 meter long **Ref. 9802060** from DN50 to DN200
- Stem extension 2 to 2,5 meter long **Ref. 9802070** from DN50 to DN200



- Tee key
 - 1 meter long square 35 mm **Ref.9802080** from DN50 to DN300
 - 1.8 meter long square 35 mm **Ref.9802081** from DN50 to DN300

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

MATERIALS DN40-65 :



Repairability :




Item	Designation	Materials DN40-65
1	Body	Ductile iron EN GJS-500-7
2	Wedge	Ductile iron EN GJS-500-7 + EPDM
3	Stem nut	Brass CuZn40Pb3
4*	Gasket bonnet	NBR
5	Bonnet screw	AISI 304
6	Stem	AISI 304
7	Bonnet	Ductile iron EN GJS-500-7
8	Holding ring	Brass CuZn39Pb2
9	O ring	NBR
10	Pusher nut	Brass CuZn39Pb2
11	Handwheel	Ductile iron EN GJS-500-7
12	Handwheel screw	AISI 304
13*	Dust-coat	NBR
14	O ring	NBR
15	O ring	NBR
16	Ring	Nylon 66
17	Auto sealing ring	NBR
18	Square drive nut	Ductile iron EN GJS-500-7

*Gaskets refs		
DN (mm)	Bonnet gasket (4)	Dust-coat (13)
40	9801260	9802123
50	9801261	
65	9802162	

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

MATERIALS DN80-300 :



Repairability :




Item	Designation	Materials DN80-300
1	Body	Ductile iron EN GJS-500-7
2	Wedge	Ductile iron EN GJS-500-7 + EPDM
3	Stem nut	Brass CuZn40Pb3
4*	Gasket bonnet	NBR
5	Bonnet screw	AISI 304
6	Stem	AISI 304
7	Bonnet	Ductile iron EN GJS-500-7
8	Holding ring	Brass CuZn39Pb2
9	O ring	NBR
10	Pusher nut	Brass CuZn39Pb2
11	Handwheel	Ductile iron EN GJS-500-7
12	Handwheel screw	AISI 304
13*	Dust-coat	NBR
14	O ring	NBR
15	O ring	NBR
16	Ring	Nylon 66
17	Auto sealing ring	NBR
18	Square drive nut	Ductile iron EN GJS-500-7

*Gaskets refs		
DN (mm)	Bonnet gasket (4)	Dust-coat (13)
80	9802163	9802124
100	9802164	9802125
125	9802165	
150	9802166	
200	9802167	9802126
250	9802168	9802127
300	9802169	9802128

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS


HANDWHEEL VALVE SIZE DN 40 - 65 (in mm) :



DN	40	50	60/65
L	140	150	170
H	190	215	235
H1	260	285	300
Ø V	200	200	200
Weight (in Kg)	7.37	8.56	12
Ref.	191040	191050	191066

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS



HANDWHEEL VALVE SIZE DN 80 - 300 (in mm) :



DN	80	100	125	150	200	250	300
L	180	190	200	210	230	250	270
H	265	315	350	385	485	600	680
H1	320	390	430	470	560	680	770
Ø V	254	254	315	315	315	406	406
Weight (Kg)	14	19.90	24.20	31.80	49.40	84.70	106
Ref.	191080	191100	191125	191150	191200-201	191250-251	191300-301

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

SQUARE DRIVE NUT SIZE (in mm) :




DN	40	50	65	80	100	125	150	200	250	300
A	14	14	14	17	17	19	19	19	24	24
B	34	34	34	34	34	36	36	36	42.5	42.5
L1	66	66	66	63	63	63	63	63	63	63
Ø D	10	10	10	10	10	10	10	10	12	12
Weight (Kg)	0.7	0.7	0.7	0.6	0.6	0.6	0.6	0.6	0.7	0.7
Ref.	9801831	9801831	9801831	9801832	9801832	9801833	9801833	9801833	9801834	9801834


RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

STEM EXTENSION SIZE (in mm) :

FIXED TYPE




TELESCOPIC TYPE



Ref.	DN	H	H1	Weight (Kg)
9802020	50-300	1000	-	3.7
9802031	50-300	1250	-	4.2
9802042	50-300	1500	-	4.5
9802060	50-200	1300	1800	9.6
9802070	50-200	2000	2500	11.8

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS

FLANGES PN10/16 SIZE (in mm) :



* DN60/65 double drilling

PN	PN10/16								PN10		
DN	40	50	60/65*	65	80	100	125	150	200	250	300
Ø C	84	99	114	118	132	156	184	211	266	319	370
Ø D	150	165	185	185	200	220	250	285	340	405	460
Ø K	110	125	135/145	145	160	180	210	240	295	350	400
Nb x Ø L	4 x 19	4 x 19	4 x 19	4 x 19	8 x 19	8 x 19	8 x 19	8 x 23	8 x 23	12 x 23	12 x 23
b	19	19	19	19	19	19	19	19	20	22	24.5
e	3	3	3	3	3	3	3	3	3	3	4
Ref.	191040	191050	191066	191065	191080	191100	191125	191150	191200	191250	191300

FLANGES PN16 SIZE (in mm) :


PN	PN16		
DN	200	250	300
Ø C	266	319	370
Ø D	340	405	460
Ø K	295	355	410
Nb x Ø L	12 x 23	12 x 28	12 x 28
b	20	22	24.5
e	3	3	4
Ref.	191201	191251	191301

RESILIENT SEAT GATE VALVE PN10/16 SHORT PATTERN DIN 3202-F4 ATC EPDM ACS


STANDARDS :

- Manufacturer certified ISO 9001 :2015 and ISO 14001 : 2015
- DIRECTIVE 2014/68/EU : For liquids of Group 2
 - Products excluded (article 1, § 2b)
- Certificate 3.1 on request
- Designing according to DIN EN 1171
- Pressure tests according to EN 12266-1, Rate A
- Length according to EN 558 series 14 (DIN 3202 F4)
- Flanges according to EN 1092-2 PN10/16
- English water agreement WRAS for the wedge EPDM coated from DN50 to 500
- French water agreement **A.C.S. N° 25 ACC LY 163**
- **GSK** Certified Epoxy Powder Coating


INSTALLATION POSITIONS :




Recommended :



Acceptable :



Non acceptable :



ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages. The customer must check the right choice of the products with the real service conditions.

Sferaco 90 rue du Ruisseau 38297 St Quentin Fallavier Tel: + 33 (0) 474.94.15.90 Fax: + 33 (0) 474.95.62.08 Internet: www.sferaco.com E-mail : info@sferaco.fr